


Table Lamps | 220-240 V | 1xE27 **8966** 



Construction year	
Table La Installation position Installation position Installation environment Power Installation environment Indoor Power Installation environment Indoor Power Installation environment Indoor Installation Indoor Installati	s - D'urbino azzi
Installation position Installation environment Indoor Power I x 11 W Lamp cap I x E27 Frequency So-60 Hz Optics General Light emission direction Garety class IP IP20 Glow wire test Direct mounting on normally flammable surfaces CE Ves Dimmable article No Directional Tilting Yes Into Indoor Indoo	
Installation environment Power  I x 11 W Lamp cap  I x E27 Frequency  Optics  General  Light emission direction  Safety class  IP  IP20 Glow wire test  Direct mounting on normally flammable surfaces  CE  Dimmable article  Directional  Tilting  Yes  Iotal angle (horizontal plane)  Walk-over  No  Drive-over  Cable included  Cable length  Electric socket  I x 11 W Indoor  A x 11 W Indoor  I x 11 W I x 127  I x 207  I	Lamps
Power         1 x 11 W           Lamp cap         1 x E27           Frequency         50-60 Hz           Optics         General           Light emission direction         downwa upward           Safety class         2           IP         IP20           Glow wire test         No           Direct mounting on normally flammable surfaces         Yes           CE         Yes           Dimmable article         No           Directional         No           Tilting         Yes           total angle (horizontal plane)         90 °           Walk-over         No           Drive-over         No           Cable included         Yes           Cable length         2 m           Electric socket         Type L	
Lamp cap 1 x E27 Frequency 50-60 H: Optics General Light emission direction downwa upward Safety class 2 IP IP20 Glow wire test No Direct mounting on normally flammable surfaces Yes CE Yes Dimmable article No Directional No Tilting Yes total angle (horizontal plane) 90 ° Walk-over No Drive-over No Cable included Yes Cable length 2 m Electric socket Type L	
Frequency 50-60 Hz Optics General Light emission direction downwa upward Safety class 2 IP IP20 Glow wire test No Direct mounting on normally flammable surfaces Yes Dimmable article No Directional No Tilting Yes total angle (horizontal plane) 90 ° Walk-over No Drive-over No Cable included Yes Cable length Electric socket Type L	W
Optics General  Light emission direction downwa upward  Safety class 2  IP IP20  Glow wire test No Direct mounting on normally flammable surfaces Yes  CE Yes Dimmable article No Directional No Tilting Yes total angle (horizontal plane) 90 °  Walk-over No Drive-over No Cable included Yes Cable length Electric socket Type L	7
Light emission direction  Safety class  2  IP  IP20  Glow wire test  No  Direct mounting on normally flammable surfaces  CE  Yes  Dimmable article  No  Directional  No  Tilting  Yes  total angle (horizontal plane)  Walk-over  No  Drive-over  No  Cable included  Yes  Cable length  Electric socket  Monard  Advantage  IP20  IP20  No  No  Por  Por  Por  Por  Por  Por	Hz
Light emission direction upward  Safety class 2  IP IP20  Glow wire test No Direct mounting on normally flammable surfaces Yes  CE Yes Dimmable article No Directional No Tilting Yes total angle (horizontal plane) 90 °  Walk-over No Drive-over No Cable included Yes Cable length Electric socket Type L	al Lighting
IP IP20 Glow wire test No Direct mounting on normally flammable surfaces Yes CE Yes Dimmable article No Directional No Tilting Yes total angle (horizontal plane) 90 ° Walk-over No Drive-over No Cable included Yes Cable length 2 m Electric socket Type L	vard and d
Glow wire test No Direct mounting on normally flammable surfaces Yes CE Yes Dimmable article No Directional No Tilting Yes total angle (horizontal plane) 90 ° Walk-over No Drive-over No Cable included Yes Cable length 2 m Electric socket Type L	
Direct mounting on normally flammable surfaces  CE  Yes  Dimmable article  No  Directional  No  Tilting  Yes  total angle (horizontal plane)  Walk-over  No  Drive-over  No  Cable included  Yes  Cable length  Electric socket  Yes  Yes  Yes  No  Type L	
CE Yes Dimmable article No Directional No Tilting Yes total angle (horizontal plane) 90 ° Walk-over No Drive-over No Cable included Yes Cable length 2 m Electric socket Type L	
Dimmable article  No Directional  No Tilting  Yes total angle (horizontal plane)  Walk-over  No Drive-over  No Cable included  Yes Cable length  Electric socket  No	
Directional No Tilting Yes total angle (horizontal plane) 90 ° Walk-over No Drive-over No Cable included Yes Cable length 2 m Electric socket Type L	
Tilting Yes total angle (horizontal plane) 90 ° Walk-over No Drive-over No Cable included Yes Cable length 2 m Electric socket Type L	
total angle (horizontal plane)  90 °  Walk-over  No  Drive-over  No  Cable included  Yes  Cable length  2 m  Electric socket  Type L	
Walk-over         No           Drive-over         No           Cable included         Yes           Cable length         2 m           Electric socket         Type L	
Drive-over No Cable included Yes Cable length 2 m Electric socket Type L	
Cable included Yes Cable length 2 m Electric socket Type L	
Cable length 2 m Electric socket Type L	
Electric socket Type L	
Resin potting No	_
Net weight 1,195 Kg	Kg





Finishing diffus	er
Material	Aluminium
Colour	embossed white RAL 9003
Processing	Coating
Finishing base	
Material	PU

## **Fante**



Table Lamps | 220-240 V | 1xE27 **8966** 

Single emission table lamps for indoor application. LED lamplamp included, lamp cap 1xE27.

The diffuser is made of aluminium with a coating treatment. The ingress protection degree is IP20; the total weight is of 1,195 kg.

. The power supply cable is included and features a 2 m lenght.

The device features protection class II and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features	
Source lumens	1520 lm
Colour temperature	2700 K
Colour rendering index	80 Ra